

**RESIN DISPERSION EXCELLENT IN LOW-TEMPERATURE HEAT SEALING PROPERTY**

Patent Number: JP3091514  
Publication date: 1991-04-17  
Inventor(s): INAGAKI HAJIME; others: 03  
Applicant(s): MITSUI PETROCHEM IND LTD  
Requested Patent: 英 JP3091514  
Application Number: JP19890227788 19890902  
Priority Number(s):  
IPC Classification: C08F255/02 ; C08F255/04 ; C08F255/08  
EC Classification:  
Equivalents: JP2839907B2

**Abstract**

**PURPOSE:** To obtain a resin dispersion excellent in low-temperature heat-sealing properties by using a modified PP powder obtained by evaporating a resin dispersion, prepared by dispersing a modified PP in a solid state in an organic solvent, to dryness at ordinary temperature so that the powder may have specified properties.

**CONSTITUTION:** A resin dispersion prepared by dispersing a modified PP at least partially graft-modified with an unsaturated carboxylic acid or its anhydride in a solid state in an organic solvent, wherein a modified PP powder obtained by evaporating this dispersion to dryness at ordinary temperature has the following properties A-D: (A) the melting point as measured by differential thermal analysis is 120-160 deg.C, (B) the degree of crystallinity as measured by X-ray diffractometry is 50-below 70%, (C) the intrinsic viscosity is 0.3-1.5dl/g, and (D) the content of the unsaturated carboxylic acid or its anhydride is 0.1-10wt.%. This dispersion can be used as an adhesive for polyolefin and is excellent in low-temperature heat sealing properties.

Data supplied from the esp@cenet database - 12